

## Single 5/2.5m

### Applications

Schools  
Recreation  
Commercial  
Industrial Estates  
Parks  
  
Solar Park sand Wind Farms

### Features

Hard to climb  
Difficult to cut through  
Good delay factor  
Good visibility  
Cost effective

### Specification

#### Mesh:

The panels comprise single 5mm wires and single 5mm vertical wires. The mesh is 200 x 50mm. The standard panel is 2500mm wide and is available in heights 1000mm to 2400mm as standard with an option for higher panels or multilift

#### Fixings:

Individual fixing brackets.  
Bolts: Anti-vandal M8 x 40mm  
Fixings: Bolts set at 400mm max.

Option: unistrut fill length channel strip

#### Post Section:

Constructed in 60mm x 60mm x 2mm hollow section steel. Posts are set at 3000mm centres. 60 x 40mm posts with a unistrut fill length channel strip are available

#### Finish:

Galvanised and polyester powder coated  
Standard colours: RAL 6005 green, 9005 black, 5010 blue, 3000 red, 9010 white  
Other colours: All other RAL colours available.



*Robust, easy to install fencing systems offering an aesthetically pleasing low maintenance, solution to security requirements. The combination of height, strength and appearance makes these ideal fences for a wide range of applications from commercial and industrial to educational .*



Matrix Fencing Systems Ltd

PO Box 4115, Bath BA1 0FN Tel: 01225 830119 Fax: 01225 830755

Mob: 07540 724715 [www.matrixfencing.co.uk](http://www.matrixfencing.co.uk)

[sales@matrixfencing.co.uk](mailto:sales@matrixfencing.co.uk) Contact: James Sanders

