

Playspec

Applications

Playgrounds

Features

Meets requirements of BS EN 1179

ROSPA approved

Self Closing gates complement this system



Playspec playground fencing together with the Prosafe self closing gates with dual action anti-slam hydraulic gate closers provides a safe fence for children to play within.

Specification - Playspec

Standard heights: 1000 and 1200mm

Posts: 50 x 50 RHS set at 2800mm centres

Verticals: 12 mm or 16mm

Horizontal Rails: Mild Steel flat, size dependent on bar infill

Fixings: Domed headed bolts, permacone security fixings and special angle cleats which allow the panels to be stepped 0 – 16mm and 56 – 72mm on site.

Finish: Hot Dip Galvanised to BS EN ISO 1461 or Galvanised and Polyester Powder Coated.

Specification - Prosafe Gates

Standard heights: 1000mm and 1200mm.

Length: Actual gate 1100mm.

Between posts 1205mm.

Integral anti-finger stop mechanism.

Slamplate with rubber buffer.

Dual action concealed hydraulic unit.

Posts nutserted to take Playspec. fencing.

Finish: Hot Dip Galvanised to BS EN ISO 1461 or Galvanised and Polyester Powder Coated.

Standard colours are Yellow RAL 1021 or Red RAL 3000.



Matrix Fencing Systems Ltd

PO Box 4115, Bath BA1 0FN Tel: 01225 830119 Fax: 01225 830755

Mob: 07540 724715 www.matrixfencing.co.uk

sales@matrixfencing.co.uk Contact: James Sanders

