

Single 5/3m

Applications

Schools
Recreation
Commercial
Industrial Estates
Parks

Solar Park sand Wind Farms

Features

Hard to climb
Difficult to cut through
Good delay factor
Good visibility
Cost effective

Specification

Mesh:

The panels comprise single 6mm wires and single 5mm vertical wires. The mesh is 200 x 50mm. The standard panel is 3000mm wide and is available in heights of 1800mm, 2000mm and 2400mm as standard with an option for higher panels.

Fixings:

Individual fixing brackets. Bolts:
Anti-vandal M8 x 40mm

Post Section:

Constructed in 60mm x 60mm x 2mm hollow section steel. Posts are set at 3000mm centres.

Finish:

Galvanised and polyester powder coated
Standard colours: RAL 6005 green, 9005 black, 5010 blue, 3000 red, 9010 white
Other colours: All other RAL colours available.



Robust, easy to install fencing systems offering an aesthetically pleasing low maintenance, solution to security requirements. The combination of height, strength and appearance makes these ideal fences for a wide range of applications from commercial and industrial to educational.



Matrix Fencing Systems Ltd

PO Box 4115, Bath BA1 0FN Tel: 01225 830119 Fax: 01225 830755

Mob: 07540 724715 www.matrixfencing.co.uk

sales@matrixfencing.co.uk Contact: James Sanders